

Roof for double trommel and cleaning brush

TopSpin PreCleaner

6 mm screwable abrasion plates for the silo

Permanent drum magnet with slide



Additional conveyor belts (extended possible)

Rip blades



Different types of Trommels:
- conic
- single
- punched
- and more

Additional internal wire screens optional 40 - 80 mm



MULTI SCREEN® MS6700-ST

Additional external wire screens optional 2 to 80 mm

Flood lamps



Bisection of the inner trommel 75 x 75 mm

Special lacquering



Remote control



All details are subject to technical modifications and future developments.
Further transfer and any kind of publication is permitted only with written approval of the Zemmler Siebanlagen GmbH.

Base frame:

longitudinal beam: profile HEA 160

Drum:

drum length: 6,700 mm
 inner drum diameter: 1,500 mm
 outer drum diameter: 2,005 mm
 inner screening surface: 31.6 sqm
 outer screening surface: 31.5 sqm
 revolving speed: 5 - 15 rpm, optional continuously adjustable with frequency converter
 slope: Standard 3°, optional manual adjustable (3°, 5°, 7°)

drive:

electric motor 22,0 kW

mesh size:

inner mesh size: 80 x 170 mm (standard)
 outer mesh size: optional - exchangeable wire screens, standard 20 x 20 mm

cleaning brush:

500 mm diameter, electric powered, electric motor 1,5 kW

Dimension:

total height: 3,200 mm
 total width: 2,500 mm
 total length: 7,500 mm

Weight:

c. 6.000 kg

Capacity:

50 - 180 cbm/hour, depending on condition of material, mesh size and feeding

Screening material:

sand, saw dust, wood chips, compost, soil, glass, coal and cinder, construction waste and recycling materials, stones and gravel sand with grain size 2 - 80 mm

3 Products:



1. product: 2 - 80 mm, on demand (standard screen size: 20 x 20 mm)
2. product: between 2 and 80 mm und up to 170 mm
3. product: ex 170 mm (standard)

Colour / Coats:

one-layer coating
 chassis, engine cover and side covers, RAL 6001 green
 screening drum: grey

Remodeling to 2 product trommel possible:

Shortened inner trommel, omission of belt of coarse product
 Shortened inner trommel, omission of middle product, widened & extended conveyor of coarse product 4.500x1.000mm
 Single trommel, omission of middle product, widened & extended conveyor of coarse product 4.500x1.000mm)



All details are subject to technical modifications and future developments.

Further transfer and any kind of publication is permitted only with written approval of the Zemmler Siebanlagen GmbH.